



Modeling the Residence Time Distribution In a Batch Fermentor: Comparison of CFD Prediction with Experiment

Dutta, Abhishek; Lencastre Fernandes, Rita; Heins, Anna-Lena; Eliasson Lantz, Anna; Jensen, Anker Degn; Gernaey, Krist; Nopens, Ingmar

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Dutta, A., Lencastre Fernandes, R., Heins, A-L., Eliasson Lantz, A., Jensen, A. D., Gernaey, K., & Nopens, I. (2011). *Modeling the Residence Time Distribution In a Batch Fermentor: Comparison of CFD Prediction with Experiment*. Abstract from 2011 AIChE Annual Meeting, Minneapolis, MN, United States. <http://aiche.confex.com/aiche/2011/webprogram/Paper236951.html>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



[Start](#) | [Grid View](#) | [Browse by Day](#) **OR** [Group/Topical](#) | [Author Index](#) | [Keyword Index](#) | [Personal Scheduler](#)

Modeling the Residence Time Distribution In a Batch Fermentor: Comparison of CFD Prediction with Experiment

Wednesday, October 19, 2011: 8:30 AM

[Symphony I/II \(Hilton Minneapolis\)](#)

Abhishek Dutta¹, [Rita Lencastre Fernandes](#)², Anna-Lena Heins³, Anna Eliasson Lantz³, Anker D. Jensen², Krist V. Gernaey² and Ingmar Nopens¹, (1)Biomath, University of Ghent, Ghent, Belgium, (2)Department of Chemical and Biochemical Engineering, Technical University of Denmark, Kgs. Lyngby, Denmark, (3)Department of Systems Biology, Technical University of Denmark, Kgs. Lyngby, Denmark

Continuous stirred tank reactors (CSTR) are ubiquitously used as fermenters in the biotechnological production of enzymes, pharmaceuticals, metabolites, antibodies, etc. They are also used in the bioprocess industry for the production of bio-ethanol, bio-hydrogen and even in mammalian cell culture. In most cases, a scale-up of these processes is necessary to yield commercial success and viability. As with most scaling-up operations, mixing is also a crucial parameter in a biological process and is often not ideal when operating at industrial scale. Poor mixing in a CSTR may be caused by gas by-passing and back-mixing phenomena leading to the formation of dead zones where, in the case of a bioreactor, cells will experience a limited supply of nutrients and oxygen. In large-scale bioreactors gradients of e.g. substrate, oxygen and pH arise as a result of non-ideal mixing, resulting in a spatially heterogeneous extracellular environment. This fact has been suggested to be the main reason behind lower product yields, but higher cell viability, in comparison to lab scale cultivation (Enfors et al., 2001)

Understanding bioreactor hydrodynamics in general, and non-ideal mixing in particular, is a key problem to understand the inherent bioprocess. The Residence Time Distribution (RTD) is one such way to characterize the non-ideal mixing in a CSTR (Choi et al., 2004). To estimate the RTD, a glucose tracer study has been performed experimentally in a Sartorius CPlus[™] batch bioreactor, having a working capacity of 10 litres, and the results were compared using Computational Fluid Dynamics (CFD) simulations. Several cases with varying impeller speed have been considered to study the effect of mixing phenomena on the RTD. The mean and variance of the distribution are analyzed for the extent of the deviation of the reactor behavior from its ideal state. Furthermore, the sensitivity of the sliding mesh is tested by varying the position of the interface zone. This would eventually contribute to building an optimized model of the bioreactor, and will be used for integration with biological models aiming at improving performance prediction in the cases of poorly-mixed reactors.

Reference

- [1] Enfors, S.O., Jahic, M., Rozkov, A., Xu, B., Hecker, M., Jørgen, B. et al. (2001). Physiological responses to mixing in large scale bioreactors. *J. Biotechnol.*, 85, 175-185.
- [2] Choi, B.S., Wan, B., Philyaw, S., Dhanasekharan, K., Ring, T.A. (2004). Residence Time Distribution in a stirred tank: comparison of CFD predictions with experiment. *Ind. Eng. Chem. Res.*, 43, 6548-6556.

Extended Abstract: File Not Uploaded

See more of this Session: [Mixing In the Production of Biopharmaceuticals](#)
See more of this Group/Topical: [North American Mixing Forum](#)